

APKU(S)-125W

GaAs + GaN Technology

THE SMALLEST OUTDOOR 125W Ku-Band BUC High Temp +70C



FEATURES:

- Robust, Light Package Design Only 9.2lbs (4.2kg)
- Extreme Stability, Reliability and Performance
- Built-in HPA Overdrive Circuit Protection
- High Temperature Mode - up to +70°C
- Built-in Optimized Linearization
- Built-in Receive Band Reject Filter
- Built-in Anti Vibration Technology
- Extreme GaN Linearity and Efficiency
- Exceeds ALL IESS-308/309 Phase Noise Standards
- Triple protection sealed waveguide output
- Field Replaceable IP68 150,000 hr Rated Fans
- Assembled and Rigorously Tested in California
- 3 Year Warranty



DESIGN OVERVIEW:

The "PHANTOM" series Extended (13.75 - 14.5GHz) and Standard (14.0 - 14.5GHz) Ku-Band BUCs are the next generation of the World's Most efficient and compact size BUCs in the industry, weighing only 9.2lbs (4.2kg) and handling output power of 125W at the Extended Ku-Band frequencies.

PERFORMANCE SPECIFICATIONS

Operating RF Frequency	APKS 14.0-14.5 GHz APKU 13.75-14.5 GHz
Operating IF frequency	950-1450 MHz 950-1700 MHz
Local Oscillator	13.05 GHz 12.8 GHz
Rated Output Power PSAT	125W 51 dBm
Linear Power SR @ -26dBc PLIN	90W 49.5 dBm
IMD3 (two tones) 3dB Back Off	-25 dBc max. 2 signal 5MHz apart at P-LINEAR
Spectral Regrowth at PLINEAR (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2dB back-off from rated power)	-30 dBc
10MHz External Ref. (Internal High Stability Optional)	10MHz Ref. Level: 0dBm +/- 5dBm Internal Ref. Stability +/- 0.1 ppm

COMPLIANCE INFORMATION

MIL - STD - 188/164C	MIL - STD - 461	ROHS, REACH, WEEE
MIL - STD - 810E	DO - 160 G	

SPURIOUS & PHASE NOISE

In-Band/Out-band Spurious	-60dBc max.	
Group Delay	Ripple 1 nsec point to point max.	
AM/PM Conversion	1.0°/dB max. at 3 dB output backoff	
Noise Power Density (TX)	-85dBm/Hz	
Noise Power Density (RX)	-155dBm/Hz (10.95 - 12.75 GHz)	
Phase Noise (Up Converter) (Ext. Ref.)	-55 dBc/Hz @ 10 Hz	-115dBc/Hz
	-65 dBc/Hz @ 100 Hz	-135dBc/Hz
	-75 dBc/Hz @ 1 kHz	-150dBc/Hz
	-85 dBc/Hz @ 10 kHz	-155dBc/Hz
	-95 dBc/Hz @ 100 kHz	-160dBc/Hz

POWER CONSUMPTION

125W 51 dBm PSAT	590W
90W 49.5 dBm PLIN	440W

PROTECTION

VOLTAGE	OVERTEMP	VSWR
SMART ALARMS IN THE M&C	MICROPHONIC	CURRENT

ENVIRONMENT SPECIFICATIONS

Environmental MIL-STD	Compliant with MIL-STD810E
Vibration MIL-STD	MIL-STD810F, Method 514.5 C-2 Transport
Operating Temperature Range	- 40° C to + 70°C
Storage Temperature Range	- 60°C to + 85°C
Fan Rating / Field Replaceable	IP 68, Field Interchangeable
Humidity	100% Condensing, IP67 Rated
Shock	20 g peak, 11 msec, 1/2 sine
Altitude	21,500ft, 6,500m

M&C INTERFACE

Advanced Monitor & Control	Ethernet Web Page Based, SNMP, RS232/485, FSK (opt.)
ALARMS	PLL LOCK, HPA, VSWR, MUTE, TX
Stealth PLin Operation Mode	LED Shut-Off Silenced fans

MECHANICAL SPECIFICATIONS

Dimensions (DC Powered)	8.5" x 5.2" x 4.54" (215x132x114 mm) Without Connectors
Weight (DC Powered)	9.2lbs (4.2kg)

PART NUMBERING SYSTEM

AP - "PHANTOM" MODEL SERIES
 KU - Universal Ku-Band 13.75 - 14.50 GHz
 KS - Standard Ku-Band 14.0 - 14.50 GHz
 80 | 100 | 125 - Rated Power in Watts
 N | F - 50 Ohm or 75 Ohm IF Input Connector Type
 R - 10 MHz Ref. Auto Sense | Internal Reference
 K - FSK Option
 U - Universal Mounting Bracket
 J - Weatherproof DC/RJ45 Cable Dongle
 C xxxx - Custom RAL Color Code
 L - Custom Language
 P - Custom Part number
 B - Custom Label
 G - Custom Logo
 T- Redundancy Ready
 H - High Gain (+79dB - 82dB)
 W - Weatherproof Pelican Style Case
 O - Other Custom Option
 X- Custom Cable



Visit Product Page

INPUT|OUTPUT INTERFACE

IF Connector	N-type (50 Ohm) F-type (75 Ohm)
Universal Prime Power via 3pin Power Connector	+ 85-260 VAC
Aphenol PT02E-12-3P, Current protection	
Output VSWR	1.5:1
Output Interface	WR75 Sealed & Grooved
Input VSWR	1.5:1
10MHz External Ref. (Internal High Stability +/- 0.1ppm Option Available)	10MHz Ref. Level: 0dBm +/- 5dBm Internal Ref. Stability +/- 0.1 ppm

GAIN

Gain (Temperature Compensated)	75dB(min) 80 dB(typ.)
TX Gain Flatness	± 0.75 dB max. over 40 MHz
TX Gain variation 50MHz	± 0.5 dB
TX Gain variation 500MHz	± 1.5 dB
Built-in Receive Reject Filter	Suppression by +20 dB (min.)

