

ASKU(S,D)-16W



16W Fanless Slim Ku-Band BUC for specific applications

FEATURES:

- Hyper-Light Package Design Only 3.3 lbs
- Extreme Stability, Reliability and Performance
- High Temperature Mode - up to + 70°C
- Built-in HPA Overdrive Circuit Protection with over-temp shut down
- Built-in Optimized Linearization to specific power
- Built-in Anti Vibration Technology
- Built-in DC Input Noise Suppression Filter
- Extreme GaN Linearity and Efficiency
- Exceeds ALL IESS-308/309 Phase Noise Standards
- Triple protection sealed waveguide output
- Fan-less Design (Customer cooling baseplate required)
- Built-in Internal Reject Filter
- 3-Year Warranty



DESIGN OVERVIEW:

The "SLIM FAN-LESS BRICK" series Extended (13.75 - 14.5 GHz), Standard (14.0 - 14.5 GHz) and Dual (13.75 - 14.5 GHz | 14.0 - 14.5 GHz) Frequency Ku-Band BUCs are the next generation of the World's Most efficient and compact size BUCs in the industry, weighing only 3.3 lbs (1.5 kg) and handling output power of 16W (min) at the Extended Ku-Band frequencies.

PERFORMANCE SPECIFICATIONS

Operating RF Frequency	ASKS 14.0 - 14.5 GHz
	ASKU 13.75 -14.5 GHz
	ASKD 13.75 -14.5 14.0 - 14.5 GHz
Operating IF frequency	950 - 1450 MHz 950 - 1700 MHz
Local Oscillator	13.05 GHz 12.80 GHz
Rated Output Power PSAT	16W 42.0 dBm
Linear Power SR @-26 dBc PLIN	13W 41.0 dBm
IMD3 (two tones) 3 dB Back Off	-25 dBc max. 2 signal 5 MHz apart at P-LINEAR
Spectral Regrowth at P-LINEAR (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2 dB back- off from rated power)	-30 dBc
10 MHz External Ref. (Internal High Stability Optional)	10 MHz Ref. Level: 0 dBm +/- 5 dBm Internal Ref. Stability +/- 0.1 ppm

SPURIOUS & PHASE NOISE

In-Band/Out-band Spurious	-55 dBc max.	
Group Delay	Ripple 1 nsec point to point max.	
AM/PM Conversion	1.0°/dB max. at 3 dB output backoff	
Noise Power Density (TX)	-85 dBm/Hz	
Noise Power Density (RX)	-135 dBm/Hz (10.95 - 12.75 GHz)	
Phase Noise (Up Converter) (Ext. Ref.)	-55 dBc/Hz @ 10 Hz	-115 dBc/Hz
	-65 dBc/Hz @ 100 Hz	-135 dBc/Hz
	-75 dBc/Hz @ 1 kHz	-150 dBc/Hz
	-85 dBc/Hz @ 10 kHz	-155 dBc/Hz
	-95 dBc/Hz @ 100 kHz	-160 dBc/Hz

POWER CONSUMPTION

16W 42.0 dBm PSAT	85W
13W 41.0 dBm PLIN	65W

COMPLIANCE INFORMATION

MIL-STD-188/164C	DO-160G	ROHS, REACH, WEEE
MIL-STD-461E		

PROTECTION

VOLTAGE	OVERTEMP	VSWR
SMART ALARMS IN THE M&C	MICROPHONIC	CURRENT

ENVIROMENT SPECIFICATIONS

Environmental MIL-STD	Compliant with MIL-STD810E
Vibration MIL-STD	MIL-STD810F, Method 514.5 C-2 Transport
Operating Temperature Range	- 40° C to + 70° C
Storage Temperature Range	- 60° C to + 85° C
Humidity	100% Condensing, IP67 Rated
Shock	20 g peak, 11 msec, 1/2 sine
Altitude	50,000 ft, 15,240 m
Cooling	Customer Supplied Mounted Cooling Baseplate

GAIN

Gain (Temperature Compensated)	66 dB (min) 70 dB (typ.)
TX Gain Flatness	± 0.75 dB max. over 40 MHz
TX Gain variation 50 MHz	± 0.5 dB
TX Gain variation 500 MHz	± 1.5 dB

PART NUMBERING SYSTEM

AS - "SLIM FAN-LESS BRICK" MODEL SERIES
KU - Universal Ku-Band 13.75 - 14.50 GHz
KS - Standard Ku-Band 14.0 - 14.50 GHz
KL - Low Ku-Band 12.75 - 13.25 GHz
KD - Dual Ku-Band 13.75 - 14.50 GHz | 14.0 - 14.50 GHz
16 | 20 | 30 | 40 | 50 - Rated Power in Linear Watts
N | F - 50 Ohm or 75 Ohm IF Input Connector Type
M - Full M&C Option RS232/485, SNMP, Ethernet
R - 10 MHz Ref. Auto Sense | Internal Reference
K - FSK Option
U - Universal Mounting Bracket
J - Weatherproof DC/RJ45 Cable Dongle
C xxxx - Custom RAL Color Code
L - Custom Language
P - Custom Part number
B - Custom Label
G - Custom Logo
T - Redundancy Ready
H - High Gain (+79 dB - 82 dB)
W - Weatherproof Pelican Style Case
O - Other Custom Option
X - Custom Cable

INPUT|OUTPUT INTERFACE

IF Connector	N-type (50 Ohm) F-type (75 Ohm)
Universal Prime Power via IF or MS/M&C Connector (7.0 A Current Limit Protection Through Coax)	+ 18-55 VDC
Output VSWR	1.3:1
Output Interface	WR75 Grooved
Input VSWR	1.5:1
RX Rejection	Internal RX Reject Filter



M&C INTERFACE

Advanced Monitor & Control	Ethernet Web Page Based, SNMP, RS232/485, FSK (opt.)
ALARMS	PLL LOCK, HPA, VSWR, MUTE, TX
Stealth PLIN Operation Mode	LED Shut-Off

MECHANICAL SPECIFICATIONS

Dimensions	6" x 4.41" x 1.82" (152 x 112 x 43.7 mm) Without Connectors
Weight	3.3 lbs (1.5 kg)

WR75 SEALED WAVEGUIDE OUTPUT



Visit Product Page